

# GAM-CAB-H35-XXX

## General purpose

GAM-CAB wire isolators are manufactured from stainless steel cables.

The particular advantages of these elements are due to their large deformation capability for shock absorption purposes and the unusually good vibration damping caused by the friction between the individual wires when the cables deform.

## Applications

Especially suitable for sensitive mobile equipment, heavy rotating machines, avionics, shipboard electronics and many vibration sensitive devices


## Specifications

NATO, STANAG, MIL, GAM-EG-13

## Codifications

The reference is: GAM-CAB-H35-XXX-FF  
FF corresponding to the fastening variant  
**Particular achievements can be proposed**

## Dimensions



Type	Ø (0,1mm)	L (mm)	b (mm)	p (mm)	q (mm)	d (mm)	W	Weight ca. g
H	35	127	114,3	8	14,0	6,5	10	130-160

P/N	Ø (0,1mm)	L (mm)	H (mm)	B (mm)	Number of windings (mm)
H35-001	35	127	40	45	10
H35-002	35	127	50	60	10



## Construction (Standards or special designs)

### Cable:

Stainless steel 1.4301 (AISI 304)  
Stainless steel 1.4401 (AISI 316)

### Bars:

Aluminium 3.3211, chromised (6061)  
Aluminium 3.3547, chromised (5083)  
Stainless steel 1.4301/1.4401/1.4571

### Screws:

Steel, galvanised

### Connections:

Stainless steel 1.4401 (AISI 316)  
Stainless steel 1.4571 (AISI 316 Ti)  
(mounting screws are not included)

### Thread inserts:

Stainless steel 1.4300 (AISI 302)

### Temperature range:

-70°C to +260°C

### Electrical conductivity:

Electrical resistance <  $2 \cdot 10^{-3} \Omega$

### Tolerances:

Fastening holes :  $\pm 0,2\text{mm}$   
Element width and height :  $\pm 2\text{mm}$

### Deflection datas:


$\pm 10\%$  for compression and tensile  
 $\pm 20\%$  for all the directions

# GAM-CAB-H35-XXX

## Fastenings variants (referred to the inner side of the bars)

The GAM-CAB wire dampers connections on the unit and the foundation can be freely selected. The following variants are possible and should be quoted when ordering :

- (\*) = through holes in both bars (standard design) (without additional information after the type designation)
- F = countersunk holes to DIN 74Bm on one bar and through holes on one bar
- FF = countersunk holes to DIN 74Bm on both bars
- M = on bar with metric threaded holes, and one bar with through holes
- MM = both bars with metric threaded holes
- FM = one bar with countersunk holes to DIN 74Bm and one bar with metric threaded holes



## Characteristics

P/N	Weight (kg)	Fixing Bores (mm)	Load Direction	Max. Static Load (daN)	Static Deflection (mm)	Dynamic stiffness (N/mm)	Natural Frequency (Hz)	Max. Load (kN)	Max. Deflection (mm)
H35-001	0,16	6,5/M6	Axial (-)	22	5	65	8,7	0,60	22
			Axial (+)	22	3	180	14,4	1,00	8
			Radial (±)	8	4	40	11,3	0,35	15
H35-002	0,17	6,5/M6	Axial (-)	8	5	28	9,4	0,32	30
			Axial (+)	8	4	47	12,2	0,41	13
			Radial (±)	3	5	11	9,6	0,25	28